

METAPACE

Metapace C-1 – The new Dimension of Card printing

www.metapace.com

Highlights

- Professional card printer for ID cards, name tags, customer cards and much more
- Produces plastic cards in full-colour and top quality 12 dots/mm (300 dpi)
- Single or automatic feed for a minimum of 100 cards
- Includes card printing software with wide range of functions (full version)
- Optionally with magnetic or smart cards as well as RFID encoder

Technical specifications

Print

Technology	Dye sublimation (colour), thermal transfer (monochrome)
Printing speed	Multicoloured: 26sec.; mono: 4 sec.
Printing pages	Single-sided (option: double-sided)
Resolution	12 dots/mm (300 dpi)
Colour	Full colour (16.7 million colours)
Feeder	Single feeder, multi-feeder (min. 100 pcs.); output tray (min. 70 pcs.)
Ink Ribbon	200 cards/roll (YMCKO); 500 cards/roll (KO)

Electronics

CPU	32 Bit processor
Memory	16MB
User interface	LCD, LED, switch
Power supply	Input: AC 100V ~ 240V; 50Hz ~ 60Hz; output: DC 24V
Fonts	True Type fonts via Windows driver
Pulse life	1 x 108 pulses; print head abrasion: 50 km

Cards

Quality and dimensions (WxL)	PVC - ISO CR-80-ISO 7810; (53.98x85.7x0.2mm ~ 1.2mm)
------------------------------	--

Encoding (options)

Magnetic stripe	ISO7811 (track 1,2,3), HiCo/LoCo
Contact (IC)	ISO7816, EMV, K-cash
Contactless (RF)	ISO14443 A,B, ISO 15693, MiFare

Interfaces

I/F Ports	USB 2.0, RS232; optional: Ethernet 10/100Mbps (TCP/IP)
-----------	--

Software

Drivers	Windows 2000, XP (32 Bit), Vista (32 Bit), Windows 7 (32 Bit)
---------	---

Environment


Operating temperature	0°C ~ 50°C
Storage temperature	-25°C ~ 70°C
Humidity	20% ~ 90% RH (non-condensing)

Housing

Dimensions (WxHxD)	192x202x403mm
Weight	5.5 kg

Warranty

Period	24 months
--------	-----------



**PROFESSIONAL
SOFTWARE
INCLUDED**



**C-1
METAPACE**