

METAPACE



- Professional direct thermal label printer in a complete package
- Maximum label width: 112 mm, maximum speed: 127 mm/sec.
- PSU and 3-fold interface (serial, parallel and USB onboard) included
- Ethernet and/or version with auto-cutter optional
- Integrated dispenser as standard

Specifications

Printing method	Direct thermal
Print width	25.4 mm ~ 104 mm
Colour	White
Print speed	127 mm/s
Paper supply method	Easy paper loading
Resolution	8 dots/mm (203dpi)
Character set	7 bitmap fonts, 7 code page, expandable up to 4x, soft font storage BMP, PCX graphic supported
Paper type	Thermal paper
Paper roll diameter	130 mm (outer) / 25.4 ~ 38.1mm (inner)
Reliability	MCBF : 12 months, auto cutter: 6 months, TPH : 6 months
Bacodes	Code 39, Code 128, interleave 2 of 5, Coda Bar, UPC-A, UPC-E, EAN-8, EAN-13, UCC-EAN128, Maxicode(2D), QR Code(2D), PDF 417(2D)
Emulation	SLCS, EPL II, ZPL II, ESC/POS
Drivers	Windows 95/98/ME/2000/NT/XP/2003/VISTA, OPOS (receipt only)
Sensors	Gap, black mark, notch sensor, continuous fan-fold
Receive buffer size	32K bytes
Interfaces	RS232C, IEEE1284, USB (all standards), Ethernet
Options	Auto cutter, manual cutter, wall mount bracket, splash proof cover
Power supply	AC 100 ~240V ± 10% (included), DC 24V, 3.75A
Dimensions (mm)	184 (W) x 221 (L) x 171 (H)
Warranty	24 months



Unpack & get started
Triple interface integrated

Your Dealer

Subject to change without notice.

www.metapace.com