

Panasonic Product Overview



| | JS-950WS »Stingray« Page 284 | JS-925WS Page 285 |
|---|--|---|
| Description | Page 284 | Page 285 |
| Display / Touch screen: | Optional: 30.5 cm (12") (resistive or capacitive), 800 x 600 pixels (SVGA), dual backlight or 38.1 cm (15") (resistive or capacitive, vertical or horizontal), 1024x768 pixels (XGA), dual backlight | Optional: 30.5 cm (12") resistive, 800 x 600 pixels (SVGA), dual backlight or 38.1 cm (15") resistive, 1024x768 pixels (SVGA), dual backlight |
| Processor: | Intel Celeron D, 3.2 GHz | Intel ATOM N270 Fanless, 1.6 GHz |
| Memory: | 512 MB, max. 2 GB | 1 GB, max. 2 GB |
| Hard disk: | Optional: hard disk 8.9 cm (3.5"), 80 GB or more; CF 4 GB or more | 6.4 cm (2.5") HDD or SSD, 80 GB |
| Operating system: | Windows 2000/XP/Vista/MS DOS 2.22, optional Windows XP Embedded preinstalled | |
| Power supply: | 230V/50 Hz | AC 100V - 240V, 50/60 Hz |
| Power consumption: | 110W. | 50W |
| Ethernet: | Ethernet 10BASE-T/100BASE-T, Wake On LAN, Boot Over LAN | Ethernet 10BASE-T/100BASE-TX, Wake On LAN |
| Interfaces | | |
| Serial: | 4 x D-SUB 9-pin (2 x optional powered) | 4x D-SUB 9-pin (2 x powered) |
| Parallel port: | 1 x D-SUB 25-pin | optional |
| Video: | 1 x D-SUB 15-polig | |
| LAN: | 1 x RJ-45 | 1 x RJ-45 |
| USB 2.0: | 4x USB (incl. 1x with 12V / 24V power supply) and 1x USB front | 4x USB (max 7x USB) |
| Keyboard: | over USB | over USB |
| Audio: | Line-In, Line-Out | optional |
| Cash drawer: | 1 x DIN 6-pin, 1 x RJ11 | 1 x RJ11 |
| PCI-Slot: | 1 x mini - PCI | no |
| Warranty: | 24 months bring-in, optionally on site | 36 months |
| Operating conditions: | 5°C–40°C, 15%–85% relative humidity, non-condensing | |
| Dimensions (WxHxD): | 250x351x282mm, display width 320mm or 364mm | 12.1": 320x392x263mm, 15": 364x413x291mm |
| Housing: | Plastic (ABS) | |
| Weight: | 11.5/12.4 kg (12"/15") | 12/13 kg (12"/15") |
| Options | | |
| Magnetic card reader, internal, tracks 1/2/3 | optional, display-mounted (left or right) | optional |
| Fingerprint reader, internal | optional, display-mounted (left or right) | no |
| Custom. displ., int.: 4 rows w. 20 char. each, fluorescent green | optional | no |
| Custom. displ., int.: 2 rows w. 20 char. each, fluorescent green | optional | optional |
| Custom. displ., int., 8.4" SVGA | optional | no |
| Dallas waiter lock, internal, magnetic | optional, beside display (left or right) | optional |
| Accessories | | |
| Cash drawer: | Panasonic JS-170CD-E30, or various models of different manufacturers | |
| Floppy disk drive: | USB, external | |
| Protec. sheets f. touch screen: | no | no |

Panasonic System Accessories

| Accessory | suitable for | Description | Item number |
|-------------------------------------|------------------|---|---------------|
| • Windows XP embedded | JS-930/935/950WS | Windows XP embedded (only available with »staging«) | panstwin |
| • Memory module 512 MB | JS-790/930/935WS | Memory module 512 MB (only available with »staging«) | 512MB RAM |
| • Configuration | All systems | Customer-specific configuration, e.g. installation of options and operating systems | Staging |
| • CF card – 4 GB | JS-790/950WS | Industrial CF card | panstcf |
| • HDD 40 GB | JS-790WS | Hard disc 40 GB for JS-790WS | HDD 40GB |
| • Card reader | JS-790WS | Integrable 3-track magnetic card reader for JS-790WS | JS-790MG-020 |
| • Customer display | JS-790WS | Integrable customer display, 2x20 characters, fluorescent green | JS-790RD-010 |
| • Extension board | JS-790WS | Interface module with 2x serial, 1x parallel, 1x cash drawer port, 1x Line Out | JS-790CB-010 |
| • Display module 30.5 cm capacitive | JS-950WS | 800x600 resolution with capacitive touch panel | JS-950D2C020 |
| • Display module 38.1 cm capacitive | JS-950WS | 1024x768 resolution with capacitive touch panel, for horizontal and vertical installation | JS-950D5C020 |
| • Display module 30.5 cm resistive | JS-950WS | 800x600 resolution with resistive touch panel | panst12r |
| • Display module 38.1 cm resistive | JS-950WS | 1024x768 resolution with resistive touch panel, for horizontal and vertical installation | panst15r |
| • Storage module 8.9cm 80 GB | JS-950WS | Hard disc module with 8.9cm hard disc, 80GB capacity | panstfp80 |
| • Storage module CF card | JS-950WS | Module for CF cards (CF card is ordered separately) | JS-950HCF010 |
| • Magnetic card reader module | JS-950WS | 3-track display-mounted reader (left or right) | panstmag |
| • Fingerprint module | JS-950WS | Display-mounted (left or right) | panstfing |
| • Dallas lock module | JS-950WS | Display-mounted (left or right) | panstdall |
| • Customer display module 2 rows | JS-950WS | Integrable customer display, 2x 20 characters, fluorescent green | panstdisp2 |
| • Customer display module 4 rows | JS-950WS | Integrable customer display, 4x 20 characters, fluorescent green | JS-950RD-020 |
| • Customer display module 21.3 cm | JS-950WS | Display (800x600) with 2 loudspeakers on customer side | panstdisp8 |
| • Connection set UK | JS-950WS | Accessories and power cord – UK version | panstkituk |
| • Connection set Europe | JS-950WS | Accessories and power cord – European version | panstkiteu |
| • External customer display | JS-930/935WS | Stainless steel housing, 2x 20 characters, fluorescent green | JS-935DD-010 |
| • Advertising compartment | JS-930/935WS | Compartment for advertising panels with the format 248x186 | 80480-00-7022 |

Information

Accessories for POS Systems

Offer your customers the complete range of professional hardware from major manufacturers and market leaders for POS and Auto ID.

To meet the highest customer requirements, we offer additional equipment that is fully compatible with Panasonic POS systems. We always keep cash drawers from Mogler, Metapace and Glancetron, Epson and Bixolon receipt printers or bar code

scanners from Datalogic and Motorola available for immediate delivery. You offer your customers fast delivery of all required hardware in a complete solution of outstanding quality, performance and price.

